




MAXIMO L GENERAL CHARACTERISTICS

Applications	Street lighting
Optics	N: Narrow V14; R: Regular R-V25; A: Regular Comfort A-V05; M: M-L10; W: Wide W-V07; B: Wide B-V08; D: Extra Wide V20; F: Front-Back V10; E: Forward Wide E-L01;
Colour temperature	2: Warm White 3,000K; 8: Neutral White 4,000K;
CRI and color tolerance (SDCM)	Minimum 70, on request 80 Colour tolerance between several luminaires Max. 4 steps MacAdam
Photobiological safety class	Exempt Group
Insulation class	Class II , Class I upon request
Degree of protection	IK09
IP Grade	IP66
Wiring	Internal connections - accessibility without tools
Dimensions	553 x 311 x 221 mm
Weight	7 kg

ELECTRICAL CHARACTERISTICS

Power supply	220-240 V 50/60 Hz; 120-270 V su richiesta
Power factor	> 0,98 (at full load)
Control system	Automatic dimming system of the 'virtual midnight' type with up to 5 steps, CLO function. 1-10, DALI-2, Zhaga 18 on request
Overvoltage protection	12kV differential mode, 12kV common mode, SPD 5kA on request
Operating temperature	-20°C +50°C
Optical unit life (Ta from -10°C to 45°C)	L90 B10 > 100.000 hr

MATERIALS



Fixing	Suitable for 40 to 76 mm diameter poles Head/pole for vertical or horizontal poles, adjustable from -15° to +20°
Heatsink	Die-cast aluminium; Paint finish RAL 9007
Frame	Die-cast aluminium; Paint finish RAL 9007
Optics	Multi-layer PMMA lenses
Screen	Flat tempered glass 5 mm thick, resistant to thermal shock and impact

The characteristics of the product are subject to change and will be confirmed when the order is placed.
The values indicated are to be considered with a tolerance of +/- 5%.

** Flux tolerance +/- 5%.
Other powers and flows on request.
External connections on request.


OPTICS

Narrow V14




Asymmetrical street optics - Narrow beam
 $L / H = 0,5 \div 0,9$

Regular R-V25




Asymmetrical street optics - Medium beam
 $L / H = 0,9 \div 1,1$

Wide W-V07





Asymmetrical street optics - Wide beam
 $L / H = 1,1 \div 1,3$

Extra Wide V20




Asymmetrical optics - Very wide beam
 $L / H = 1,3 \div 1,6$

Regular Comfort A-V05





Asymmetrical Optics - Comfort
 $L / H = 1,0$

Symmetric S-SW07





Symmetrical Optics
 $L / H = 1,0$

Forward Wide E-L01




Asymmetrical optics - Very wide beam
 $L / H = 1,5-2,0$

Front-Back V10



Asymmetrical Street Optics - Front-Back
 $L / H = 1,2 \div 1,5$

Wide B-V08





Asymmetrical street optics - Wide beam
 $L / H = 1,2 \div 1,5$

** Flux tolerance +/- 5%.



Other powers and flows on request.
 External connections on request.

Roto-Wide U-V04





Rotosymmetrical road optics - Wide beam

Symmetric Z-L04

Symmetrical street optics - Medium beam
 $L / H = 1,2$

M-L10

 $L / H = 1.0$


** Flux tolerance +/- 5%.

Other powers and flows on request.

External connections on request.


DIMMING

STANDARD VIRTUAL MIDNIGHT PROFILE



For other profiles please contact the sales department.

STANDARD CLO PROFILE



** Flux tolerance +/- 5%.
Other powers and flows on request.
External connections on request.

CODING

	Optics	LED Color Temperature	Power *	Insulation Class (Input Range)	Dimming	Various
MXLG	R	8	XX	2	N	A
	N Narrow V14	2 Warm White 3,000K	02 93	2 Class II (220-240V)	N No Dimming	L Standard
	R Regular R-V25	8 Neutral White 4,000K	04 102.5	Versions available on request 1 Class I (120-270V)	M Virtual Midnight**	
	A Regular Comfort A-V05	Versions available on request	06 110.9		Z Virtual Midnight** + CLO	
	M M-L10		08 124.1		L Zhaga 18 + Virtual Midnight**	
	W Wide W-V07		10 132		Y Zhaga 18 + Virtual Midnight** + CLO	
	B Wide B-V08		12 144.1			
	D Extra Wide V20	5 Warm White 2,700K	14 157.3			
	F Front-Back V10	9 Extra Warm White 2,200K				
	E Forward Wide E-L01					

** Flux tolerance +/- 5%.

Other powers and flows on request.

External connections on request.